



Directive 2002/95/EC  
"RoHS"  
Compliant

**NOTES:**

1. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATORS: PBT GF UL 94 V-0; BLACK
3. SIGNAL CONTACTS: COPPER ALLOY; 7,5A nominal  
PLATING MATING AREA: 30µm HARD GOLD over min. 50µm NICKEL  
FEMALE CONTACTS WIRE BRIDGE FROM POS. 1 TO POS. 2
4. CONNECTOR IS PART MARKED: 13-000201 CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name	tolerance	dim. in mm	
					date	name
					drawn	20.06.07 Schmidt
					appd.	20.06.07 Koch
					norm	
					d-old	
a	Origin			<b>CONEC</b> <sup>®</sup>		

scale: 2:1	
material: see notes	
title: <b>Micro TCA Single Port</b> Female, Crimp Style with wire bridge	
dwg no: Inventor 10	DIN-A3
13K1A2076	
sh: 1	
part no: 13-000201	